



# RHP BEARING EXPORTED LTD

## 40 mm x 62 mm x 28 mm SKF GE 40 TXG3E-2LS Spherical Plain Bearings - Radial



Bearing No. GE 40 TXG3E-2LS

GE 40 TXG3E-2LS Bearing 2D drawings and 3D CAD models

Category	Spherical Plain Bearings - Radial
Inventory	4.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.32
EAN	7316571913742
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material - Outer Member	Stainless Steel
Material - Ball	Stainless Steel
Material - Liner	Teflon
Relubricatable	No
Enclosure	2 Seals
Other Features	2 Piece   Corrosion Resistance   Self Lubricating   Triple Lip Heavy Duty Seals
Long Description	40MM Bore; 22MM Housing Width; 62MM Outside Diameter; Spherical Plain; Stainless Steel Outer Member; Stainless Steel Ball; Teflon Liner; 28MM Overall Width; Not Relubricatable
Inch - Metric	Metric
Category	Plain Bearings Spherical Radial



## RHP BEARING EXPORTED LTD

UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	GE 40 TXG3E-2LS
Weight / LBS	0.705
D	2.441 Inch   62 Millimeter
d	1.575 Inch   40 Millimeter
B	1.102 Inch   28 Millimeter
Housing Width	0.866 Inch   22 Millimeter
bore diameter:	40 mm
inner ring material:	Steel
outside diameter:	62 mm
outer ring width:	22 mm
misalignment angle:	6 °
race material:	PTFE Composite
inner ring width:	28 mm
radial static load capacity:	465 kN
bearing type:	Radial
radial dynamic load capacity:	280 kN
lubrication type:	Maintenance Free/Self-Lubricating
operating temperature range:	-50 to +150 ° C ° F
closure type:	Triple Lip Seals
overall width:	28 mm
outer ring material:	Stainless Steel
manufacturer upc number:	7316571913742
Lubricant	Maintenance free – dry lubrication



## RHP BEARING EXPORTED LTD

Design (sliding contact surface combination)	Steel/PTFE fabric
Sealing solution	Triple-lip seals
d	40 mm
D	62 mm
B	28 mm
C	22 mm
	7 °
d <sub>k</sub>	53 mm
r <sub>1</sub> min.	0.6 mm
r <sub>2</sub> min.	1 mm
d <sub>a</sub> min.	43.5 mm
d <sub>a</sub> max.	45 mm
D <sub>a</sub> min.	54.5 mm
D <sub>a</sub> max.	57.5 mm
r <sub>a</sub> max.	0.6 mm
r <sub>b</sub> max.	1 mm
Basic dynamic load rating C	280 kN
Basic static load rating C <sub>0</sub>	465 kN
Specific dynamic load factor K	300 N/mm <sup>2</sup>
Specific static load factor K <sub>0</sub>	500 N/mm <sup>2</sup>
Mass plain bearing	0.32 kg